


ANSI / ASME B18.2.1



Technical Specification of Hex Head Tap Bolts

Gewindedurchmesser	Width Across Flat (AF) Schlüsselweite		Width Across Corner (AC) Eckenweite		Höhe (H)	
	Inch	mm	Inch	mm	Inch	mm
1/4	7/16	11,112	0.505 - 0.488	12.83 - 12.40	5/32	3,969
5/16	1/2	12,700	0.577 - 0.557	14.66 - 14.15	13/64	5,159
3/8	9/16	14,288	0.650 - 0.628	16.51 - 15.95	15/64	5,953
7/16	5/8	15,875	0.722 - 0.698	18,34 - 17,30	9/32	7,14
1/2	3/4	19,050	0.866 - 0.840	22.00 - 21.34	5/16	7,938
9/16	13/16	20,638	0.938 - 0.910	23.83 - 23.11	23/64	9,128
5/8	15/16	23,812	1.083 - 1.051	27.51 - 26.70	25/64	9,922
3/4	1-1/8	28,575	1.299 - 1.254	32.99 - 31.85	15/32	11,906
7/8	1-5/16	33,338	1.516 - 1.447	38.51 - 36.75	37/64	14,684
1	1-1/2	38,100	1.732 - 1.653	43.99 - 41.99	43/64	17,065
1 1/4	1-7/8	47,625	2.165 - 2.066	54.97 - 52.48	27/32	21,432

Maße können durch Toleranzen bei der Fertigung von Massenteile abweichen